

Pubhub Reader (Web)

Embedding the reader on your site

The reader may be embedded through an `iframe`, however, for the best experience we recommend embedding it directly on to your site:

1. Include reader scripts/styling

Replace `2.1.3` with the required version:

```
<script defer="defer" type="module" src="//reader.pubhub.dk/2.1.3/js/chunk-vendors.js"></script>
<script defer="defer" type="module" src="//reader.pubhub.dk/2.1.3/js/app.js"></script>
<link href="//reader.pubhub.dk/2.1.3/css/chunk-vendors.css" rel="stylesheet" />
<link href="//reader.pubhub.dk/2.1.3/css/app.css" rel="stylesheet" />
<script defer="defer" src="//reader.pubhub.dk/2.1.3/js/chunk-vendors-legacy.js" nomodule></script>
<script defer="defer" src="//reader.pubhub.dk/2.1.3/js/app-legacy.js" nomodule></script>
```

2. Insert the required reader element

The id of the element *must* be `pubhub-reader`.

Don't forget to replace the `order-id` and `close-href` attributes.

```
<div id="pubhub-reader" order-id="8b90f5f8-452b-4dff-831f-54ee1edb3800" close-href="javascript:window.
history.back()"></div>
```

The following attributes are supported:

Attribute	Description
<code>order-id</code>	Id of the order (<code>internalorderid</code>) from the library-/retailer-API.
<code>identifier</code>	ISBN/GTIN-13 of the book for sample mode.
<code>environment</code>	Pubhub-environment in which the order is created. Supported values: <code>qa</code> , <code>live</code> . Default value if omitted: <code>live</code> .
<code>close-href</code>	URL or javascript (preended with <code>javascript:</code>), which the reader's close-button executes.
<code>search-enabled</code>	Enables book content search. Default value: <code>true</code> .
<code>annotations-enabled</code>	Enables annotations. <code>content-selection-enabled</code> must be <code>true</code> in order to create annotations. Default value: <code>true</code> .

Attribute	Description
<code>content-selection-enabled</code>	Enables content selection. Default value: <code>true</code> .
<code>mouse-swipe-navigation-enabled</code>	Enables mouse swipe gestures to change pages. This may interfere with content selection unless <code>content-selection-enabled</code> is <code>false</code> . Default value: <code>false</code> .

Updating the reader

To update the reader, simply replace the version number in the url (e.g. `2.1.3`) of the scripts/stylesheets.

Confidentiality

The SDK (including as integrated in, or utilized by any Application) is the confidential and proprietary information of Publizon, and you may not, during the term or thereafter, disclose them to any third party, or to use them for any purpose other than as expressly provided herein, without a separate written agreement with Publizon authorizing you to do so.